

## 1320 3/8" BUTTERFLY IMPACT WRENCH



- Provides 80 ft-lb of torque at a free speed of 10,000 RPM
- Weighing only 1.1 lb. and with an overall length of only 5.4", it fits comfortably in the operator's palm
- Ideal for work around radiators and in other very space restricted areas
- Features a three position built-in power management switch for control on the job
- Built-in swivel air inlet increases maneuverability and access to restricted work areas
- Double hammer mechanism reduces vibration while increasing reliability

## 1075-TH / 1055-TH 3/8" & 1/2" COMPACT IMPACT WRENCH



- Low weight aluminum alloy housing
- Reliable Jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "Silencing Technology" reduces the noise level to 89 dBA
- Trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation

## SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max Torque (ft-lb)	Weight (kg)	Length (in.)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
1320	10,000	1/2	3/8	1800	80	0.54	5.4	8	3/8	1/4	6.0
1055-TH	9,000	1/2	1/2	1600	500	1.27	4.25	6	3/8	1/4	9.9
1075-TH	9,000	1/2	3/8	1600	500	1.27	4.25	6	3/8	1/4	9.9

## 1076-XL 3/8" COMPOSITE COMPACT IMPACT WRENCH



- Provides 550 ft-lb maximum torque
- Low weight composite housing reduces weight to 2.5 Lbs.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "silencing technology" reduces the noise level to 85 dba
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- New patented trigger mounted combined reverse & power management switch provides ultimate control and one-hand operation
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil, provide ultimate reliability

## 1056-XL 1/2" COMPOSITE COMPACT IMPACT WRENCH



- Provides 550 ft-lb maximum torque
- Low weight composite housing reduces weight to 2.5 lbs.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "Silencing Technology" reduces the noise level to 85 dBA
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- New patented trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil, provide ultimate reliability

### SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
1076-XL	9,000	9/16	3/8	1650	550	1.18	4.25	8	3/8	1/4	9.9
1056-XL	9,000	9/16	1/2	1650	550	1.18	4.25	8	3/8	1/4	9.9

## 1300-TH-A 3/8" IMPACT WRENCH



- Provides 500 ft-lb loosening torque
- "Super Clutch" Twin Hammer Mechanism
- Durable composite housing
- Patented ergonomically designed housing
- Patented quiet tuned exhaust (86 Decibels)
- Patented easy operation flip lever forward and reverse

## 1355-XL 3/8" "XTREME POWER" IMPACT WRENCH



- Provides industry leading 700 ft-lb of loosening torque
- The NitroCat 1355-XL is a no non-sense, hard hitting 3/8" impact wrench that incorporates the twin hammer mechanism
- Provides all the torque you need and tremendous speed to get the job done
- Patented quiet tuned exhaust (86 dBA)
- Patented easy operation flip lever forward and reverse
- Great for brake calipers, transmission work
- Durable Kevlar™ reinforced "Body Armour" housing

## SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
1300-TH-A	10,000	1/2	3/8	1750	450	1.36	6.75	6	3/8	1/4	10.5
1355-XL	10,000	1/2	3/8	1350	500	1.36	6.0	6	3/8	1/4	10.5