

## 5100-A-T COMPOSITE AIR HAMMER



5100-A

- 3,000 Blows per minute for fast cutting action
- High performance and low weight
- Multi-patented muffler/exhaust system gives this tool an extremely low noise of 88 dBA and vibration level of 4.2 m/sec<sup>2</sup>
- High quality safety-lock retainer for ease of chisel change and added safety
- Model 5100-A Includes: Blow Mold Kit, 5 Pc. Chisel Set and Quick Change Retainer

## 5200-A-T COMPOSITE LONG STROKE AIR HAMMER



- 2100 blows/minute provide hard hitting cutting action
- 3-3/4" Piston Stroke
- Vibration damped technology reduces the vibration level to 4.2 m/sec<sup>2</sup>
- Patented AIRCAT design double injection composite grip has been ergonomically designed to provide unmatched comfort for the user
- Patented AIRCAT silencing technology
- Heavy duty ball-lock quick change chisel retainer adds safety and reliability

## 5300-A-T SUPER DUTY 0.498" SHANK AIR HAMMER



5300-A

- 0.498" Shank opening
- 1760 Blows / minute
- Heavy duty "Quick Change Chisel Retainer" prevents chisels by-passing conventional spring retainers
- Patented AIRCAT ergonomically designed grip provides unmatched comfort for the user
- Designed for ultra heavy duty and for driving out shackle and king-pins and cutting large bolts, nuts and fasteners
- Model 5300-A Includes: 4 Pc. Chisel Set

## SPECIFICATIONS

Model No.	Free Speed (BPM)	Pistol Stroke	Shank Opening	Retainer	Valve	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
5100-A-T	3,000	2-5/8	.401"	Safety-lock	Plate	1.91	7.6	6	3/8	1/4	4.2
5200-A-T	2,100	3-3/4	.401"	Safety-lock	Plate	2.27	11.0	6	3/8	1/4	4.2
5300-A-T	1,760	2-11/16	.498"	Quick Change	Plate	2.63	8.94	6	3/8	1/4	17.4