

1320 3/8" BUTTERFLY IMPACT WRENCH



- Provides 80 ft-lb of torque at a free speed of 10,000 RPM
- Weighing only 1.1 lb. and with an overall length of only 5.4", it fits comfortably in the operator's palm
- Ideal for work around radiators and in other very space restricted areas
- Features a three position built-in power management switch for control on the job
- Built-in swivel air inlet increases maneuverability and access to restricted work areas
- Double hammer mechanism reduces vibration while increasing reliability

1075-TH / 1055-TH 3/8" & 1/2" COMPACT IMPACT WRENCH



- Low weight aluminum alloy housing
- Reliable Jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "Silencing Technology" reduces the noise level to 89 dBA
- Trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max Torque (ft-lb)	Weight (kg)	Length (in.)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1320	10,000	1/2	3/8	1800	80	0.54	5.4	8	3/8	1/4	6.0
1055-TH	9,000	1/2	1/2	1600	500	1.27	4.25	6	3/8	1/4	9.9
1075-TH	9,000	1/2	3/8	1600	500	1.27	4.25	6	3/8	1/4	9.9

1076-XL 3/8" COMPOSITE COMPACT IMPACT WRENCH



- Provides 550 ft-lb maximum torque
- Low weight composite housing reduces weight to 2.5 Lbs.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "silencing technology" reduces the noise level to 85 dba
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- New patented trigger mounted combined reverse & power management switch provides ultimate control and one-hand operation
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil, provide ultimate reliability

1056-XL 1/2" COMPOSITE COMPACT IMPACT WRENCH



- Provides 550 ft-lb maximum torque
- Low weight composite housing reduces weight to 2.5 lbs.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "Silencing Technology" reduces the noise level to 85 dBA
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- New patented trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil, provide ultimate reliability

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1076-XL	9,000	9/16	3/8	1650	550	1.18	4.25	8	3/8	1/4	9.9
1056-XL	9,000	9/16	1/2	1650	550	1.18	4.25	8	3/8	1/4	9.9

1375-XL 1/2" "XTREME POWER" IMPACT WRENCH



- Provides industry leading 700 ft-lb of loosening torque
- The NitroCat 1375-XL is a no non-sense, hard hitting 1/2" impact wrench that incorporates the twin hammer mechanism
- Provides all the torque you need and tremendous speed to get the job done
- Patented quiet tuned exhaust (86 dBA)
- Patented easy operation flip lever forward and reverse
- Great for brake calipers, transmission work
- Durable Kevlar™ reinforced "Body Armour" housing

1000-TH / 1000-TH-2 1/2" IMPACT WRENCH



- Provides 1,000 ft-lb loosening torque
- "Super Clutch" twin hammer mechanism
- Durable composite housing
- Patented ergonomically designed handle
- Patented quiet tuned exhaust (86 Decibels)
- Patented easy operation flip lever forward and reverse



**1000-TH-2
2" Ext. Anvil**

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb)	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1375-XL	10,000	1/2	1/2	1350	500	1.36	6.0	6	3/8	1/4	11.80
1000-TH	8,000	9/16	1/2	1300	800	2.00	7.5	8	3/8	1/4	7.40
1000-TH-2	8,000	9/16	1/2x2	1300	800	2.09	9.5	8	3/8	1/4	7.40

1150 1/2" IMPACT WRENCH



- Provides 1,295 (ft-lb) loosening torque
- Most powerful 1/2" impact in it's class!
- Hard hitting twin hammer mechanism
- Durable composite housing
- Patented ergonomically designed handle
- Patented quiet tuned exhaust (86 Decibels)
- Patented easy operation flip lever forward and reverse



WATCH REVIEW

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb)	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1150	9,000	9/16	1/2	1400	900	2.09	7.5	8	3/8	1/4	8.1

1295-XL 1/2" COMPACT IMPACT WRENCH



- Provides 1,150 ft-lb loosening torque
- The shortest length full size 1/2" impact wrench available!
- One hand operation and control - unique "one click" fwd/rev
- Protected design" hammer cage front flange reduces vibration to 4.45 m/sec²
- Internal "Silencing Technology" reduces the noise level to 88 dBA
- The patented grip has been ergonomically designed to fit perfectly fit the hand providing unmatched comfort for the user
- The "protected design" air rotor rear support eliminates the rotor moving forward and scratching the front end cap-increasing tool life and reliability

1250-K 1/2" KEVLAR™ TWIN CLUTCH IMPACT WRENCH



- Provides 1,300 ft-lb Loosening torque
- The NitroCat 1250-K is a fearless, hard hitting, 1/2" impact wrench that out performs anything in its class!
- Hard hitting smooth twin clutch mechanism
- Durable Kevlar™ reinforced "Body Armor" housing
- Patented ergonomically designed handle
- Patented quiet tuned exhaust (86 dBA)
- Patented easy operation flip lever forward and reverse
- The twin clutch is better suited for heavy duty (frame work, medium to heavy duty trucks)

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb)	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1295-XL	7,500	9/16	1/2	1600	900	2.09	6.62	8	3/8	1/4	4.45
1250-K	8,500	9/16	1/2	1000	950	2.18	8.25	8	3/8	1/4	6.5

1450 1/2" IMPACT WRENCH



- Provides 800 ft-lb max. torque
- Refined design twin hammer increases blow frequency and blow efficiency
- Very fast torque development
- 9,000 RPM Free speed provides fast run-down
- Ergonomically designed grip provides maximum operating comfort
- Six position power management switch in back cap provides ultimate control
- Great balance and handling comfort
- Brushed aluminum housing finish

1450-2 1/2" x 2" IMPACT WRENCH



- Provides 800 ft-lb max. torque
- Refined design twin hammer increases blow frequency and blow efficiency
- Very fast torque development
- 9,000 RPM free speed provides fast run-down
- Ergonomically designed grip provides maximum operating comfort
- Six position power management switch in back cap provides ultimate control
- Great balance and handling comfort
- Brushed aluminum housing finish

SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb)	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec ²)
1450	9,000	9/16	1/2	1200	800	2.63	7.0	8	3/8	1/4	13.5
1450-2	9,000	9/16	1/2 x 2	1200	800	2.81	9.0	8	3/8	1/4	14.0