

## 807 3/8" "MINI" COMPOSITE PALM RATCHET



- 35 ft-lb Maximum torque
- 300 RPM provides fast run-down
- **Built-in quick socket release button**
- Ergonomic composite over mold grip provides comfort
- Great for work around radiators and very confined spaces
- Only 5.4" long and weighs only 1.1 lbs.

## 800 1/4" "MINI" COMPOSITE SINGLE PAWL RATCHET



- 35 ft-lb Maximum torque
- Strongest 1/4" Ratchet in its class!
- Single pawl mechanism
- Fast rundown 320 RPM
- Superior internal mechanics
- Patented quiet tuned exhaust (82 dBA)
- Feather trigger for control
- Ergonomically designed housing
- Most comfortable trigger lever in the industry

## 801 3/8" "MINI" COMPOSITE SINGLE PAWL RATCHET



- 35 ft-lb Maximum torque
- Strongest 3/8" Mini Ratchet in its class!
- Single pawl mechanism
- Fast rundown 320 RPM
- Superior internal mechanics
- Patented quiet tuned exhaust (82 dBA)
- Feather trigger for control
- Ergonomically designed housing
- Most comfortable trigger lever in the industry

## SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive(in.)	Working Torque	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
807	300	3/8	3/8	5-25 ft-lb	35	0.36	5.4	3	3/8	1/4	5.7
800	320	3/8	1/4	5-35 ft-lb	35	0.54	8.5	4	3/8	1/4	2.3
801	320	3/8	3/8	5-35 ft-lb	35	0.54	8.5	4	3/8	1/4	2.3

## 802 3/8" COMPOSITE TWIN PAWL RATCHET



- 70 ft-lb Maximum torque
- Durable twin pawl mechanism
- Fast rundown 280 RPM
- Patented quiet tuned exhaust (82 dBA)
- Feather trigger for control
- Ergonomically designed housing
- Most comfortable trigger lever in the industry

**802-5 available with 1/2" square drive**

## 804 1/4" MINI RATCHET



- 30 ft-lb Maximum torque
- 280 RPM provides fast run-down
- The single piece, high grade, alloy steel housing ratchet head increases reliability and eliminates "loosening" of the ratchet head
- Uniquely designed transmission gear increases the rate of torque build-up
- Ergonomic composite over mold grip provides comfort

## 806 3/8" HIGH PERFORMANCE RATCHET



- 80 ft-lb Maximum torque
- 200 RPM
- Strongest 3/8" ratchet in its class!
- Unique variable speed throttle provides unmatched control
- Enlarged ratchet head provides added reliability
- Ratchet head protective cover adds protection
- Soft touch coated handle grip increases operating comfort
- Needle bearing construction increases reliability
- 360° Rotational exhaust allows exhaust air to be directed as preferred

## SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive(in.)	Working Torque	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
802	280	3/8	3/8	5-70 ft-lb	70	1.18	10.5	4	3/8	1/4	3.2
802-5	280	3/8	1/2	5-70 ft-lb	70	1.18	10.5	4	3/8	1/4	3.2
804	280	3/8	1/4	N/A	30	0.73	7.15	4	3/8	1/4	N/A
806	200	1/2	3/8	N/A	80	1.18	10.9	4	3/8	1/4	5.0

## 805-HT 3/8" HIGH TORQUE RATCHET



- **130 ft-lb Maximum torque**
- Latest design ratchet head eliminates "spreading"
- Reliable single pawl design
- Extra large ratchet head increases reliability
- Rapid response and variable speed trigger
- Quiet for such a powerful ratchet (84 dBA)
- Ergonomically designed contoured grip and trigger provide ultimate operating comfort

**WARNING:** Use with care to avoid finger trapping.

## 805-HT-5 1/2" HIGH TORQUE RATCHET



- **130 ft-lb Maximum torque**
- Latest design ratchet head eliminates "spreading"
- Reliable single pawl design
- Extra large ratchet head increases reliability
- Rapid response and variable speed trigger
- Quiet for such a powerful ratchet (84 dBA)
- Ergonomically designed contoured grip and trigger provide ultimate operating comfort

**WARNING:** Use with care to avoid finger trapping.

## SPECIFICATIONS

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Max. Torque (ft-lb) @90 psi	Weight (kg)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet (in.) BSP	Vibration (m/sec <sup>2</sup> )
805-HT	180	5/8	3/8	130	1.45	12.45	6	3/8	1/4	6.6
805-HT-5	180	5/8	1/2	130	1.45	12.45	6	3/8	1/4	6.6