

AIRAMMER®



SOLUTIONS THAT LAST



AIRRAMMER®

The Airmammer® is a pneumatically powered rammer. It eliminates a long list of engine related problems. There are no fuel or fuel mixing issues, no carburetor, no spark plug, no rewind starter, no flooding problems, no air or fuel filters that can be plugged, no rpm issues, all of which affect performance.

The Airmammer also offers the following advantages:

- No need to handle flammable gas or oil
- Lower maintenance cost \$\$
- Motor is closer to the gearbox for better balance
- No exhaust fumes, safe for indoor use
- Easier to run and maneuver
- Can be transported or stored in any position
- No frustration of trying to start an engine
- No stopping to refuel
- Less time spent on pre-run check over, i.e. check oil, clean air filter, fuel up, etc.
- Less down time for routine maintenance

SPECIFICATIONS	AR56	AR57
Operating Weight	124 lb (56 kg)	126 lb (57 kg)
Height	35.0 in (89 cm)	35.0 in (89 cm)
Width	13.5 in (34 cm)	13.5 in (34 cm)
Length	24.75 in (63 cm)	24.75 in (63 cm)
Shoe W x L	IRON 11 x 13 in (28 x 33 cm)	ALUM 13 x 15 in (33 x 38 cm)
Percussion Rate	650 blows/min	650 blows/min
Travel Speed	60 ft/min (18.3 m/min)	60 ft/min (18.3 m/min)
Compaction Depth	Up to 24 in* (61 cm)	Up to 24 in* (61 cm)
Air Required	75 cfm 100 psi	75 cfm 100 psi
RPM	4500	4500

() Metric Measurements.
Specifications subject to change without notice.

* Clean sand, optimum moisture. MBW recommends that lifts not exceed 12" of granular soil or 9" cohesive soil.



AUTHORIZED DISTRIBUTOR

PML-Limited

Patch Park • Ongar Road • Abridge • Romford • RM4 1AA

Tel: 01708 688222 • Fax: 01708 688122

E-mail: info@pml-limited.co.uk • Website: www.pml-limited.co.uk